



**ZASTAVA
KAMIONI**



New Turbo Rival 4x2



ZASTAVA KAMIONI

ZASTAVA KAMIONI d.o.o, Kragujevac

- u restrukturiranju

Kosovska 4 · 34000 Kragujevac · Republika Srbija

tel: ++381 34 336 160 · fax: ++381 34 335 319

e-mail: prodaja@zastava-kamioni.co.rs

www.zastava-kamioni.co.rs






New TurboRival 4x2

TIP I VRSTA MOTORA	EURO 3	SOFIM 8140.43S - Dizel, četiri takta sa direktnim ubrizgavanjem goriva, (COMMON RAIL)
RADNA ZAPREMINA (cm ³)		2800
MAKSIMALNA SNAGA PRI 3600 o/min.		92 kW / 125 KS
MAKSIMALNI OBRтни MOMENT PRI 1800 o/min.		290 Nm
VRSTA HLAĐENJA		VOĐENO
SPOJNICA		Suva sa jednim diskom i mehaničkom komandom od 10 1/2"
MENJAČ		IVECO 2826.5 Mehanički sa 5 sinhronizovanih stepena prenosa napred i hodom nazad
KOČNICA		Hidraulična servokočnica sa ABS-om, depresorom i dva nezavisna kruga, napred disk, pozadi doboš kočnica
UPRAVLJAČ		Hidraulički sa servo dejstvom



TEHNIČKI PODACI



modeli	ŠASIJA SA KABINOM			ŠASIJA SA PRODUŽENOM KABINOM						KAMION			KAMION SA PRODUŽENOM KABINOM						FURGON			FURGON SA PODIGNUTIM KROVOM			KOMBI	MINIBUS										
	35.12H	40.12H	49.12H	35.12H	40.12H	49.12H	35.12H	40.12H	49.12H	35.12H	40.12H	49.12H	35.12H	40.12H	49.12H	35.12H	40.12H	49.12H	35.12H	40.12H	49.12H	30.12H	40.12H	40.12H	49.12H											
OSNO RASTOJANJE (mm)	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	2800			2800			2800			3310	3310				
DUŽINA VOZILA (mm)	5740	5740	5740	5740	5740	5740	5740	5740	5740	5780	5780	5780	5915	5915	5915	5940	5940	5940	5965	5965	5965	4815			4815			4815			5965	5965				
ŠIRINA VOZILA (mm)	2000			2000			2000			2140			2140			2140			2000			2000			2000			2000								
VISINA VOZILA (mm)	2085			2085			2085			2085			2085			2085			2250			2700			2255			2700								
UNUTRAŠNJA DUŽINA TOV. SANDUKA / PROSTORA (mm)										3493	3493	3493	2801	2801	2801	2140	2140	2140	2463	2463	2463	3613	3613	3613				2463	2463	2463						
UN.ŠIRINA TOV. SANDUKA (mm)										2073	2073	2073	2073	2073	2073	2073	2073	2073				1820	1820	1820				1820	1820	1820						
VISINA TOV. SANDUKA (mm)										400	400	400	400	400	400	400	400	400				1512	1512	1512				1885	1885	1885						
ZAPREMINA TOVARNOG PROSTORA (m³)																			6.8	6.8	6.8	9.9	9.9	9.9	8.4	8.4	8.4	12.4	12.4	12.4						
VIS. PODA VOZILA OD TLA (mm)	825			825			825			1050			1050			1050			790			800			750			800								
KORISNA NOSIVOST (kg)	1580	2280	3040	1450	2150	2910	1300	2000	2760	1350	2050	2790	1220	1920	2690	1100	1800	2560	1440	1440	1440	1250	1900	2640	1460	1460	1460	1270	1920	2660	8 put.	13 put.	16 put.	19 put.		
DOZVOLJENA UKUPNA MASA (kg)	3500	4200	5000	3500	4200	5000	3500	4200	5000	3500	4200	5000	3500	4200	5000	3500	4200	5000	3500	4200	5000	3500	4200	5000	3500	4200	5000	3500	4200	5000	3170	4200	4200	5000		
PNEUMATICI	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	215/75 R16 185/75 R16	215/75 R16 185/75 R16	215/75 R16 185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16		
MAKSIMALNA BRZINA (km/h)	117	117	105	117	117	105	117	117	105	117	117	105	117	117	105	117	117	105	122 117 117	122 117 117	122 117 117	117	105	105	117	105	105	117	117	117	117					
ZAPREMINA REZ. ZA GORIVO (l)	70			70			70			70			70			70			70			70			70											

U OKVIRU POLITIKE UNAPREDJENJA PROIZVODA ZASTAVA KAMIONI MOGU BEZ PREDHODNOG OBAVEŠTENJA IZMENITI TEHNIČKE KARAKTERISTIKE.